



## SPECIFICATION SHEET

(Updated – 11/12/19)

### Technical Specifications

<b>Axle to Axle;</b>	31" +/- .125"	<b>Flex Guard Spring;</b>	4 1/2" (2 dimples)
<b>Timing;</b>	Timing Dots Even	<b>Cam Spacers;</b>	.265"
<b>Brace Height;</b>	7" +/- .125"	<b>String Stop Length;</b>	7 1/8"
<b>Centershot;</b>	.604"-.784"	<b>Cam lean;</b>	.150" Max

### Draw Lengths

MOD POS.	DRAW LENGTH	ATA RATING*
1	31"	331-328
2	30 1/2"	328-325
3	30"	323-320
4	29 1/2"	324-317
5	29"	315-312
6	28 1/2"	311-308
7	28"	305-302
8	27 1/2"	301-297
9	27"	294-291
10	26 1/2"	289-286
11	26"	283-280
12	25 1/2"	277-274

\*Estimated performance at 70lbs, 350 grains.

### String Specifications

Serving Locations								Overall Length
<b>String</b>	2 1/2"	7 15/16"	11 15/16"	15 3/16"	17 3/16"	18 5/8"	-	23 7/8"
<b>Cable</b>	11"	14"	25 1/2"	-	-	-	-	29 1/8"
<b>Upper Yoke</b>	16 1/4"	17 1/16"	18 9/16"	19 3/8"	-	-	-	35 5/8"
<b>Lower Yoke</b>	14 3/4"	15 11/16"	17 3/16"	18 1/8"	-	-	-	32 7/8"
<b>Cable Yoke</b>	3 3/4"	6 3/8"	10 5/8"	13 1/4"	-	-	-	17"

### Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80 lbs
62	59-65	70 lbs
67	64-70	65 lbs
72	69-75	60 lbs
84	81-87	50 lbs
102	99-105	40 lbs

\*All draw weights are -0/+3 lbs.