



SPECIFICATION SHEET

(Updated – 10/31/19)

Technical Specifications

Axle to Axle;	35" +/- .125"	Flex Guard Spring;	3 1/2" (4 dots)
Timing;	Timing Dots Even	Cam Spacers;	.265"
Brace Height;	6" +/- .125"	String Stop Length;	6 1/8"
Centershot;	.726-.846"	Cam lean;	.150" Max

Draw Lengths

MOD POS.	DRAW LENGTH	ATA RATING*
1	31"	337-334
2	30 1/2"	334-331
3	30"	329-326
4	29 1/2"	327-323
5	29"	321-318
6	28 1/2"	317-314
7	28"	311-308
8	27 1/2"	307-303
9	27"	300-297
10	26 1/2"	295-292
11	26"	289-286
12	25 1/2"	283-280

*Estimated performance at 70lbs, 350 grains.

String Specifications

Serving Locations	Overall Length
String	27 7/8"
Cable	33 1/8"
Upper Yoke	35 5/8"
Lower Yoke	32 7/8"
Cable Yoke	17"

Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80 lbs
62	59-65	70 lbs
67	64-70	65 lbs
72	69-75	60 lbs
84	81-87	50 lbs
102	99-105	40 lbs

*All draw weights are -0/+3 lbs.