

CENTEC NXT Specification Sheet

Version 1 on 2/4/19

Technical Specifications

Axle to Axle;	26.125" +/- .125"	Cable Guard Rod;	6.375"
Timing @ BH;	4 Dots Aligned	Cam Spacers;	0.100" on cable side
Brace Height*;	6.125" +/- .125"	String Stop Length;	6.5"

Cam System

(Draw lengths are minus nothing, plus 1/4")

MOD POS	Draw Length* (inches)	MAX. Draw WGT. (lbs.)	MIN. Draw WGT. – 10 Turns out of Limb Bolt (lbs.)	ATA RATING – 5 grains/MAX Draw WGT. (FPS)
26	26	45	20	Up to 270
25.5	25.5	42	17	Up to 265
25	25	40	15	Up to 260
24.5	24.5	40	15	Up to 255
24	24	40	15	Up to 250
23.5	23.5	40	15	Up to 245
23	23	40	15	Up to 240
22.5	22.5	40	15	Up to 235
22	22	40	15	Up to 230
21.5	21.5	40	15	Up to 225
21	21	40	15	Up to 220
20.5	20.5	40	15	Up to 215
20	20	40	15	Up to 210
19.5	19.5	40	15	Up to 205
19	19	40	15	Up to 200

*Draw Length/Brace Height are an additional 3/8" longer when the limb bolts are turned out the maximum of 10 turns.

String Specifications

Serving Locations								Overall Length
String	15"	21-5/8"	26"	28-3/4"	30-1/4"	36-1/4"	-	50-9/16"
Cable	2"	7"	9"	21-1/2"	-	-	-	26-1/2"

Limb Deflections

Deflection Number	Draw Weight @ 25"
114 (+/-3)	42-45 lbs